

# GKB Dragframe



Have you just finished renovating your natural grass or hybrid sports pitch? Do you immediately want to level the dressing soil or sand, that makes imperfections in your pitch? Do you want to provide your sports pitch with the finishing touch after the operation? Then the Dragframe is the perfect tool for you.



The Dragframe is provided with two folding side decks, which broaden the operating width to 4 m and that can be folded away by an optional hydraulic system. The spiral shaped bars of the Dragframe are developed in such a way that they ensure an even result of your operation.

After the tillage, for instance with the Ecodresser, the pitch will be levelled perfectly by the Dragframe. Optionally we can provide the Dragframe with welded mesh panels, so that you can also use the Dragframe on sand. Subsequently, you are in position to work effective and efficient on several surfaces.


**THE WORKER IS KING**



# Dragframe

*Specifications:*

Type	SR400
Working width	400 cm / 157"
Dimensions operation (l x w x h)	410 x 140 x 130 cm / 161 x 55 x 51"
Dimensions transport (l x w x h)	120 x 140 x 130 cm / 47 x 55 x 51"
Weight	200 kg / 445 lbs
Power requirement	30 - 50 hp
Coupling	Standard three-point hitch cat I - II
Option 1	Hydraulic foldable side decks
Option 2	Welded mesh panels



**THE WORKER IS KING**