



GKB Sandspreader



Do you have the aspiration to keep your sports pitch or golf course in prime condition? We know it is a challenge throughout the entire year. The GKB Sandspreader is the appropriate machine to evenly apply or spread a vast variety of materials across your pitch. For example, to spread sand on your golf course or sports pitch, during both the construction of your pitch or for maintenance purposes. With the Sandspreader you are in possession of the perfect machine to do just that.



The Sandspreader is available in four distinctive designs. The capacity of the bunker varies from 1 m³ to 4 m³. The SP100 is suitable for assembling on a turf truck. For instance, on a ProGator, Truckster or Workman.

The shape and design of the sand bunker ensures an efficient operation and ensures your clear view along the machine. The sand is transported to a metering valve by means of a conveyer belt, which, optionally, is also available as a hydraulically operated metering valve. The double, hydraulically powered, spreading discs are adjustable on multiple points, consequently, the Sandspreader enables you to create perfect sand distribution.

THE WORKER IS KING



GKB

THE WORKER IS KING



As standard, the control unit of the conveyor belt and the spreading discs, is mounted on the Sandspreader. Nonetheless, we provide the option to deliver the Sandspreader with a touchscreen, that will allow you to control these functions from the cab of your tractor. Moreover, a conveyer belt on the front will enable you to use the Sandspreader as a buffer machine.

Accordingly, we can deliver the SP100 with a wheel set containing four pivoting balloon tires. All other Sandspreader models are delivered with four pivoting balloon tires as standard, in order to assure the perfect weight distribution on your sports pitch or golf course.



The Sandspreader has been developed and produced in our Dutch, energy neutral industrial plant. All materials used are of premium quality. Take for example the S355 MC steel and Bucher hydraulics. The choice of these derives from the experience of our contractor division. Our machines can withstand harsh working conditions!

Are you making use of the public road? Then you have the optional assembly of hydraulically operated load covering panels on the top of the machine. Together with the overrun brake and the modern LED lighting system, the Sandspreader is ready to from point A to point B via the public road.



Sandspreader

Specifications:

Type	SP100	SP230	SP300	SP400
Working width	variable	variable	variable	variable
Dimensions (l x w x h)	190 x 100 x 90 cm/ 75 x 39 x 35"	400 x 185 x 160 cm/ 157 x 73 x 63"	470 x 185 x 160 cm/ 185 x 73 x 63"	470 x 245 x 190 cm/ 185 x 96 x 75"
Unladen weight	625 kg / 1380 lbs	950 kg / 2095 lbs	1125 kg / 2480 lbs	1425 kg / 3145 lbs
Capacity sandbunker	1,0 m ³	2,3 m ³	3,0 m ³	4,0 m ³
Power requirement	> 30 hp	> 40 hp	> 50 hp	> 65 hp
Linkage	Drawbar eye	Drawbar eye	Drawbar eye	Drawbar eye

The following options are only applicable to the SP100:

Option 1	Support legs SP100
Option 2	Hydraulically operated metering valve
Option 3	Wheel set swingaxle unbraked
Option 4	Wheel set braked single axle
Option 5	Hydraulic proportional operation

The following options are applicable to the SP230, SP300 and the SP400:

Option 1	Hydraulic proportional operation
Option 2	Touchscreen including proportional control block
Option 3	Hydraulically operated metering valve
Option 4	Overrun brake
Option 5	Hydraulic brake

The following option is only applicable to the SP300

Option 1	Hydraulically operated load covering panels
-----------------	---

The following option is only applicable to the SP300 and the SP400:

Option 1	Hydraulically operated elevator conveyor belt front side
-----------------	--

THE WORKER IS KING